



PROGRAMMABLE SPECTRUM CHANGES EVERYTHING

Spectrum is the most influential factor in plant development. By adjusting the ratio of colors, cultivators get precision control of their plant's full genetic poetntial.

- Target Terpenes
- Fine Tune Development

Spectrum Controls Growth







LIGHT SPECTRUM AND CHEMICAL EXPRESSION

A plant's chemical composition influences its color, flavor, aroma, and psychoactive effects. The Avici's programmable spectrum gives cultivators the power to fine tune development and unlock the plant's full genetic potential.

Target Chemical Expression

A programmable spectrum gives cultivators the tools to enhance chemical profiles for specific end uses.


Target Development


Strategically adjusting the spectrum can dramatically alter the way a plant looks, smells, and tastes, giving large scale cultivators craft level precision.




EASE OF WORKFLOW

Change seasons at the touch of a button







"Seed to harvest under one light."

Avici's seasonal presets and programmable spectrum area easily customized with Revolution's TouchMi controller for a more streamlined workflow.



ADAPTIVE

FUTURE-PROOF SPECTRUM



Lighting is the most important investment in a cultivation facility; every reaction in the plant is driven by light.

As cultivation science improves, change your spectrum with the push of a button, rather than changing lamps.

Technological Flexibility



LONGEST LASTING

150,000 Hour Rated Life



How Do We Know?

We use OSRAM's diode specifications and NASA's soldering standards to calculate our rated life.



Reliable

The Avici Series has a 150,000 hour life, three times industry standard. Cultivators can trust in the superior reliability of a high rated life.



Higher ROI

Avici stays brighter for longer, growing more cannabis and continuing to pay for itself long after other fixtures need to be replaced.



The AVICI Series

245 Series





IP67 Toplight

Racking or High Bay

245w Per Bar, High Uniformity Multiple Applications

	245 v 1	245 v 3	245 v 4
Suggested Application	Toplight	Flower	Flower
Power	245w	735w	980w
PPF	755	2,264	3,018
Footprint	2' x 4'	4' × 4'	4' x 4'
Hang Height	> 18"	> 18"	> 18"



3,018 uMole/s

IP67

The Avici provides better development and higher yield.

The V series are an easy to clean, waterproof, GMP certified solution.





Limited Lifetime Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2





Spectrum	Programmable	
PPF	3,018 uMole/sec dimmable in 1% steps	
Max Wattage	980w	
Input Current 4	.1A @ 240v, 3.5A @ 277v, 2.8A @ 347v, 2.0 @ 480v	
Input Voltage	240v, 277v, 347v or 480v	
Power Factor	0.99 @ 277 volts	
Light Source	Osram OSLON LED array	
Rated Life (LM90)	> 150,000 hours	
Operational Tempe	erature 35C	
Fixture Temperatur	re 55C	
Ingress Rating	IP67	
RMH (Recommended Mounted Height Above Canopy) > 16		
Dimming / Spectru	m Control External Controller	
Dimensions 52 x 45 x 4 inches (~ 48		





2,264 uMole/s

IP67

High output with programmable spectrum to target development.

The V series are an easy to clean, waterproof, GMP certified solution.



Limited Lifetime Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2





Progr	ammable
2,264 uMole/sec dimmable in	1% steps
	735w
A @ 240v, 2.6A @ 277v, 2.1A @ 347v, 1.	5A @ 480v
240v, 277v, 347	'v or 480v
0.99 @	277 volts
Osram OSLON	LED array
> 150,0	000 hours
ure	35C
	55C
	IP67
Mounted Height Above Canopy)	>16"
Control External (Controller
36.5 x 45 x 4 inches	(~36lbs)
	2,264 uMole/sec dimmable in A @ 240v, 2.6A @ 277v, 2.1A @ 347v, 1. 240v, 277v, 347 0.99 @ Osram OSLON > 150,0 ure Mounted Height Above Canopy) Control External (





755 uMole/s

IP67

High output with programmable spectrum to target development.

The V series are an easy to clean, waterproof, GMP certified solution.



Limited Lifetime Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2





Spectrum			Progra	ammable
PPF		755 uMole/sed	dimmable in '	1% steps
Max Wattage			245v	v per Bar
Input Current	1.1A @ 240	0.88A @ 277v,	0.71@ 347v, 0.5	51@ 480v
Input Voltage			240v, 277v, 347v	v or 480v
Power Factor			0.99 @	277 volts
Light Source			Osram OSLON L	_ED array
Rated Life (LM90)			> 150,0	00 hours
Operational Temp	erature			35C
Fixture Temperatu	ıre			55C
Ingress Rating				IP67
RMH (Recommend	ed Mounted	d Height Above	Canopy)	> 16"
Dimming / Spectro	um Control		External C	ontroller
Dimensions		45 x 5	.5 x 2.5 inches ((~12 lbs)