

# AVICI



60w  
185  $\mu$ Mole

C1

3.06 - 3.8  
 $\mu$ Mole/J Efficacy

Easily dimmable for early stages of growth.

Programmable Spectrum with high efficiency options.

## Clone Light Features



190  $\mu$ Mole in a uniform 4' x 4'



IP67 Waterproof



Ultra Low Profile for Racking



Programmable Spectrum



# AVICI C1

Limited Lifetime Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2



Spectrum	Programmable
PPF	185 uMole/sec dimmable in 1% steps
Max Wattage	60w
Input Current	0.25A @ 240, 0.27A @ 277v, 0.17@ 347v, 0.125@ 480v
Input Voltage	240v, 277v, 347v or 480v
Power Factor	0.99 @ 277 volts
Light Source	Osram OSOLON LED array
Rated Life (LM90)	> 150,000 hours
Efficacy	3.06 - 3.8 uMole/J
Operating Temperature	35C
Fixture Temperature	55C
Ingress Rating	IP67
RMH (Recommended Mounted Height Above Canopy)	> 12"
Footprint @RMH	2' x 4'
Dimming / Spectrum Control	External Controller
Dimensions	45 x 2.5 x 2.5 inches (~ 12 lbs)