

AVICI 1150



High Ceiling Application

2400 $\mu\text{Mole/s}$

The Avici provides better development and **higher yield**.

1150w

Better than 1:1, the Avici is **brighter** than an HPS DE.

AVICI 1150

Limited Lifetime
Warranty



CE Certified



DLC Listed



FCC Part 15 B



CSA Certified



RoHS and RoHS2



Spectrum	Programmable
PPF	2400 uMole/sec dimmable in 1% steps
Max Wattage	1150w
Input Current	9.6 A @ 120 volts, 4.8 A @ 240 volts, 4.17 A @ 277 volts
Input Voltage	120/240/277 volts AC, 50/60 Hz or 347v 50/60 Hz
Input Power Plug	NEMA 6-15P (240v) or NEMA 5 or NEMA L7P
Power Factor	0.99 @ 120 volts
Light Source	Osram OSOLON LED array
Rated Life (LM90)	> 150,000 hours
Efficacy	2.15 - 3.65 uMole/J
Operational Temperature	35C
Fixture Temperature	55C
Ingress Rating	IP55
RMH (Recommended Mounted Height Above Canopy)	> 18"
Footprint	5' x 5'
Dimming / Spectrum Control	External Controller
Dimensions	435mm x 528mm x 121.6mm (~ 17" x 21" x 5") 15.0 kg (~ 32 lbs)