

AVICI



60w
185 μ Mole

C1

3.06 - 3.8
 μ Mole/J Efficacy

Easily dimmable for early stages of growth.

Programmable Spectrum with high efficiency options.

Clone Light Features



190 μ Mole in a uniform 2' x 4'



IP67 Waterproof



Ultra Low Profile for Racking



Programmable Spectrum



AVICI C1

Limited Lifetime Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2



| | |
|---|--|
| Spectrum | Programmable |
| PPF | 185 uMole/sec dimmable in 1% steps |
| Max Wattage | 60w |
| Input Current | 0.25A @ 240, 0.27A @ 277v, 0.17@ 347v, 0.125@ 480v |
| Input Voltage | 240v, 277v, 347v or 480v |
| Power Factor | 0.99 @ 277 volts |
| Light Source | Osram OSOLON LED array |
| Rated Life (LM90) | > 150,000 hours |
| Efficacy | 3.06 - 3.8 uMole/J |
| Operating Temperature | 35C |
| Fixture Temperature | 55C |
| Ingress Rating | IP67 |
| RMH (Recommended Mounted Height Above Canopy) | > 12" |
| Footprint @RMH | 2' x 4' |
| Dimming / Spectrum Control | External Controller |
| Dimensions | 45 x 2.5 x 2.5 inches (~ 12 lbs) |