

AVICI

360W

1,110 μMole

High output for maximum yield and development.

M6

3.06 - 3.8

$\mu\text{Mole/J}$ Efficacy

Programmable Spectrum with high efficiency options.

Mother Light Features



500 μMole in a uniform 4' x 4'



IP67 Waterproof



Ultra Low Profile for Racking



Programmable Spectrum



AVICI M6

Limited Lifetime
Warranty



CE Certified



FCC Part 15 B



CSA Certified



RoHS and RoHS2



Spectrum	Programmable
PPF	1110 uMole/sec dimmable in 1% steps
Max Wattage	360w
Input Current	1.5A @ 240, 1.3A @ 277v, 1.0@ 347v, 0.75@ 480v
Input Voltage	240v, 277v, 347v or 480v
Power Factor	0.99 @ 277 volts
Light Source	Osram OSOLON LED array
Rated Life (LM90)	> 150,000 hours
Efficacy	3.06 - 3.8 uMole/J
Operating Temperature	35C
Fixture Temperature	55C
Ingress Rating	IP67
RMH (Recommended Mounted Height Above Canopy)	> 12"
Footprint @RMH	4' x 4'
Dimming / Spectrum Control	External Controller
Dimensions	45 x 45 x 2.5 inches (~ 20 lbs)